# **DELTA TWIN**

## 9940UOP200P63

EAN 4031582366938

Swivel castor, housing made of heavy pressed steel, bright zinc plated, blue passivated, precision ball bearing swivel head, sealed, wheel axle with nut, plate fitting. Wheel centre made of Polyamide, precision ball bearing





Picture may differ from original product


#### **Technical Data**

| Wheel diameter         | 200 mm         |
|------------------------|----------------|
| Wheel width            | 50 mm          |
| Castor width           | 157 mm         |
| Size of Plate          | 137 x 105 mm   |
| Plate hole centres     | 105 x 80/75 mm |
| Plate hole             | 11 mm          |
| Dome-Ø                 | 136 mm         |
| Offset                 | 55 mm          |
| Swivel Interference    | 323 mm         |
| Overall height         | 250 mm         |
| Temperature            | - 40 / + 85 °C |
| Standard               | EN_12532       |
| Weight                 | 5.17 kg        |
| Swivel Radius          | 161.5 mm       |
| Hardness of tread      | Shore D 75     |
| Load capacity          | 750 kg         |
| Load capacity (static) | 1500 kg        |


### Advantages at a glance

| Roll performance Movement noise | • • • • • • |
|---------------------------------|-------------|
| Attrition                       | • • • • 0   |
| Corrosion resistance            | • • • 0 0   |

#### **Dimensions**



## **Structure & Mounting**



# **DELTA TWIN**

# 9940UOP200P63

EAN 4031582366938

### **Structure & Mounting**

