5327PJP100S70

EAN 4031582367485

Swivel castor with total lock, tail end of castor, housing and wheels made from high grade synthetic materials, with integrated threadguards, all metal parts are bright zinc plated, yellow thick layer passivated, threaded stem with hexagon neck. Wheel centre made of Polypropylene, Tread: TENTEprene (thermoplastic rubber), grey non-marking, precision ball bearing , with threadguards Please read the assembly instructions in the service area of the TENTE website.

Hint: These castors are also with grey locking lever available.





Picture may differ from original product


Technical Data

| Wheel diameter | 100 mm |
|------------------------|----------------|
| Wheel width | 32 mm |
| Threaded stem | M 10 x 17 mm |
| Offset | 37 mm |
| Swivel Interference | 240 mm |
| Overall height | 137 mm |
| Temperature | - 10 / + 40 °C |
| Standard | EN_12530 |
| Weight | 0.463 kg |
| Hardness of tread | Shore A 87 |
| Load capacity | 100 kg |
| Load capacity (static) | 200 kg |


Advantages at a glance

| Roll performance | • • • 0 0 |
|----------------------|-----------|
| Movement noise | • • • • 0 |
| Attrition | • • • 0 0 |
| Corrosion resistance | • • • • ○ |

Dimensions



Structure & Mounting



5327PJP100S70

EAN 4031582367485

Structure & Mounting



