FOOT MASTER GAAD-125-ASF-HUD

EAN 4031582495171

Swivel twin wheel castor, housing made of steel welded, zinc plated, tapper roller bearing with hardened treatment in the swivel head (125/150 series: double thrust bearing), grease nipple, self-aligned function with two swiveling axes with different swiveling radii, wheel axle with nut, plate fitting. Wheel centre made of cast iron, Tread: Polyurethane, casted, precision ball bearing.






Picture may differ from original product

Technical Data

| Wheel diameter | 125 mm |
|---------------------|----------------|
| Wheel width | 35 mm |
| Castor width | 128 mm |
| Size of Plate | 145 x 145,0 mm |
| Plate hole centres | 120 x 120 mm |
| Plate hole | 11 mm |
| Dome-Ø | 128 mm |
| Offset | 33 mm |
| Swivel Interference | 200 mm |
| Overall height | 190 mm |
| Temperature | -10 / +90 °C |
| Weight | 11.85 kg |
| Swivel Radius | 100 mm |
| Load capacity | 440 kg |

Dimensions



Advantages at a glance

| Roll performance | • • • • |
|----------------------|-----------|
| Movement noise | • • • • 0 |
| Attrition | • • • • 0 |
| Corrosion resistance | • • • • • |