# **DELTA TWIN**

### 9942UOP125P63

EAN 4031582366945

Swivel castor with total lock, head end of castor, housing made of heavy pressed steel, bright zinc plated, blue passivated, precision ball bearing swivel head, sealed, wheel axle with nut, plate fitting. Wheel centre made of Polyamide, precision ball bearing





Picture may differ from original product


#### **Technical Data**

Wheel diameter	125 mm
Wheel width	46 mm
Castor width	157 mm
Size of Plate	137 x 105 mm
Plate hole centres	105 x 80/75 mm
Plate hole	11 mm
Dome-Ø	136 mm
Offset	55 mm
Swivel Interference	318 mm
Overall height	178 mm
Temperature	- 40 / + 85 °C
Standard	EN_12532
Weight	5.007 kg
Swivel Radius	159 mm
Hardness of tread	Shore D 75
Load capacity	750 kg
Load capacity (static)	1500 kg


### Advantages at a glance

Roll performance	• • • 0 0
Movement noise	• • • 0 0
Attrition	• • • • 0
Corrosion resistance	• • • 0 0

#### **Dimensions**



#### **Structure & Mounting**



# **DELTA TWIN**

## 9942UOP125P63

EAN 4031582366945

#### **Structure & Mounting**

