AGILA TWIN 2970DIK050P40

EAN 4031582302653

Swivel caster, housing made of pressed steel, bright zinc plated, blue passivated, double ball bearing swivel head, wheel axle with nut, plate fitting. Wheel center made of pressed steel, Tread: solid rubber, grey non-marking, with threadguards, cone ball bearing





Picture may differ from original product

Dimensions




Wheel diameter	1.97 in
Wheel width	0.75 in
Caster width	2.09 in
Plate size	2.36 x 2.36 in
Plate hole centers	1.89/1.50 x 1.89/1.50 in
Plate hole	0.25 in
Dome-Ø	2.09 in
Offset	0.98 in
Swivel Interference	4.17 in
Overall height	2.72 in
Temperature	-4/+185 °F
Standard	EN 12530
Weight	0.783 lbs
Swivel Radius	2.09 in
Hardness of tread	Shore A 80
Load capacity (dynamic)	130 lbs
Load capacity (static)	265 lbs


Advantages at a glance

Roll performance	$\bullet \bullet \bullet \circ \circ$
Movement noise	$\bullet \bullet \bullet \circ \circ$
Attrition	$\bullet \bullet \bullet \circ \circ$
Corrosion resistance	$\bullet \bullet \bullet \circ \circ$

© Copyright 2025 TENTE International www.tente.com 01/04/2025



Structure & Mounting



PRODUCT INFORMATION



EAN 4031582302653

Structure & Mounting

